

Joker CT	3 CT	3,5 CT	4 CT	4 CT rigid version	5 CT	6 CT	7 CT
Working width (m)	3.00	3.50	4.00	4.00	5.00	6.00	7.00
Transport width (m)	3.00	3.50	2.95	4.08	2.95	2.95	2.95
Transport height (m)	1.90	1.90	2.80	1.90	3.25	3.70	4.00
Length (m)	2.50	2.50	2.90	2.50	2.90	2.90	2.90
Length incl. Mono TG (m)	3.70	3.70	---	3.48	---	---	---
Weight (kg)	1600 - 2600	1800 - 2850	2400 - 3100	2000 - 3400	2800 - 3500	3000 - 3900	3500 - 4550
Weight incl. Mono TG (kg)	2300 - 2600	2500 - 2850	---	2900 - 3400	---	---	---
DiscSystem discs Ø (cm)	52	52	52	52	52	52	52
DiscSystem disc thickness (mm)	6	6	6	6	6	6	6
Number of DiscSystem discs (PCE)	24	28	32	32	40	48	56
Cutting angle DiscSystem discs (°)	17	17	17	17	17	17	17
DA control devices (PCE)	0 (+1 with hydr. depth adjustment)	0 (+1 with hydr. depth adjustment)	1 (+1 with hydr. depth adjustment)	0 (+1 with hydr. depth adjustment)	1 (+1 with hydr. depth adjustment)	1 (+1 with hydr. depth adjustment)	1 (+1 with hydr. depth adjustment)
Horsepower requirement (kW/hp)	65 · 90 / 90 · 120	75 · 100 / 100 · 140	90 · 120 / 120 · 160	90 · 120 / 120 · 160	110 · 150 / 150 · 200	130 · 175 / 180 · 240	205 · 260 / 280 · 350
Horsepower requirement incl. Mono TG (kW/hp)	140 / 190	160 / 220	---	180 / 245	---	---	---
Number of tines Mono TG (PCE)	5	6	---	8	---	---	---
Tine spacing Mono TG (cm)	60	59	---	50	---	---	---
Implement attachment 3-point linkage Joker CT	3-point Cat. II/III	3-point Cat. II/III	3-point Cat. III/IV	3-point Cat. II/III	3-point Cat. III/IV	3-point Cat. III/IV	3-point Cat. III/IV
Implement attachment 3-point linkage Mono TG	3-point Cat. III	3-point Cat. III	---	3-point Cat. III	---	---	---