

TECHNICAL DATA

Tiger MT	3 MT	4 MT rigid version	4 MT	5 MT	6 MT	8 MT
Working width (m)	3.00	4.00	4.00	4.80	6.00	7.50
Transport width (m)	3.00	4.05	3.00	3.00	3.00	3.00
Transport height (m)	---	---	---	---	---	4,00 / 4,15 (with levelling disc 2-row Ø 46 cm)
Length with tyre packer 7.50–16 (m)	8.30	8.60	8.60	8.60	8.60	8.60
Length with tyre packer 210 / 95 - 24 (m)	8.70	---	9.00	9.00	9.00	9.00
Length with double RollPack packer (m)	9.00	9.30	9.30	9.30	9.30	9.30
Weight (kg)	4215	5525	6575	7425	8420	10380
Number of DiscSystem discs (PCE)	14	18	20	24	28	36
Disc spacing (cm)	38	40.5	40	39	42	41
Number of tines (PCE)	7	9	9	11	13	17
Tine spacing in one row (cm)	86	94	94	91	96	90
Tine spacing (cm)	43	47	47	45.5	48	45
Frame height (mm)	850	850	850	850	850	850
DA control devices lower link	2 (+1 with marker)	3 (+1 with marker)	3 (+1 with marker)	3 (+1 with marker)	3 (+1 with marker)	---
DA control devices adjustable drawbar	---	---	4 (+1 with marker)	4 (+1 with marker)	4 (+1 with marker)	---
Horsepower requirement (kW/hp)	110 - 220 / 150 - 300	150 - 270 / 200 - 370	150 - 270 / 200 - 370	185 - 295 / 250 - 400	220 - 400 / 300 - 550	275 - 440 / 375 - 600
Tyre packer size / Ø (cm)	7.50 – 16 AS / 78 cm or 210 / 95 – 24 AS / 100 cm	7.50 – 16 AS / 78 cm	7.50 – 16 AS / 78 cm or 210 / 95 – 24 AS / 100 cm	7.50 – 16 AS / 78 cm or 210 / 95 – 24 AS / 100 cm	7.50 – 16 AS / 78 cm or 210 / 95 – 24 AS / 100 cm	7.50 – 16 AS / 78 cm or 210 / 95 – 24 AS / 100 cm
Double RollPack packer Ø (cm)	62	62	62	62	62	62
Lower link linkage	Cat. III - III / IV - IV	Cat. III - III / IV - IV	Cat. III - III / IV - IV	Cat. III - III / IV - IV	Cat. III - III / IV - IV	Cat. III - III / IV - IV
Adjustable drawbar linkage hitch	---	---	Bolt Ø 50 mm	Bolt Ø 50 – 70 mm	Bolt Ø 50 – 70 mm	Bolt Ø 70 mm
Adjustable drawbar linkage hitch ball joint	---	---	Hitch Ø 51 mm	Hitch Ø 51 – 71 mm	Hitch Ø 51 – 71 mm	Hitch Ø 71 mm
Adjustable drawbar linkage ball head	---	---	K 80	K 80	K 80	K 80