

TECHNICAL DATA

Maestro RV / RX	6 RV	8 RV	9 RV	12 RV	6 RX	8 RX	9 RX	12 RX
Transport width (m)	3.00	3.00	3.00	3.00	3.00	3.00	3.00	3.00
Transport height (m)	3.10	3.90	4.00	3.90	3.10	3.90	4.00	3.90
Length without seed wagon (m)	2.90 (3.50 incl. micro-granular compound hopper)	2.90 (3.50 incl. bout markers or micro-granular compound hopper)	2.90 (3.50 with bout markers)	2.90 (3.50 incl. bout marker or micro-granular compound hopper)	2.90 (3.75 incl. micro-granular compound hopper)	3.30 (3.75 incl. bout markers or micro-granular compound hopper)	3.30 (3.75 with bout markers)	3.30 (3.75 incl. bout marker or micro-granular compound hopper)
Transport length with Pronto 6 AS (m)	---	10.85	---	10.85	---	10.95	---	10.95
Transport length with Focus TD 3-point (m)	---	11.25	---	11.25	---	---	---	---
Transport length with Focus ST 3-point (m)	---	11.15	---	11.15	---	---	---	---
Weight without seed wagon (kg)	1600	2000	2200	2700	1900	2300	2450	3000
Weight with Pronto 6 AS (kg)	---	6700	---	7500	---	7000	---	7800
Weight with Focus TD 3-point (kg)	---	11200	---	11900	---	---	---	---
Weight with Focus ST 3-point (kg)	---	11500	---	---	---	---	---	---
Capacity seed container (l)	70	70	70	70	70	70	70	70
Number of rows	6	8	9	12	6	8	9	12
Max. coulter pressure hydr. tractor attachment (kg)	150 - 180	150 - 180	150 - 180	150 - 180	150 - 180	150 - 180	150 - 180	150 - 180
Max. coulter pressure hydr. with optional weight transfer tractor attachment (kg)	---	---	---	---	150 - 310	150 - 290	150 - 280	150 - 240
Max. coulter pressure hydr. with seed waggon (kg)	---	150 - 350	---	150 - 350	---	150 - 350	---	150 - 350
Depth control wheel Ø (cm)	40	40	40	40	40	40	40	40
Press wheels Ø (cm)	30 / 33	30 / 33	30 / 33	30 / 33	30 / 33	30 / 33	30 / 33	30 / 33
Catching roller	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Row spacing (cm)	70 / 75 / 80	70 / 75 / 80	60 / 70 / 75	45 / 50	70 / 75 / 80	70 / 75 / 80	60 / 70 / 75	45 / 50
Sowing depth (cm)	1.5 - 9	1.5 - 9	1.5 - 9	1.5 - 9	1.5 - 9	1.5 - 9	1.5 - 9	1.5 - 9
Drop height seed (cm)	45	45	45	45	45	45	45	45
Operational speed (km/h)	2 - 12	2 - 12	2 - 12	2 - 12	2 - 15	2 - 15	2 - 15	2 - 12
Horsepower requirement (kW/hp)	74 / 100	110 / 150	118 / 160	125/170	81 / 110	118 / 160	125 / 170	132/180
Horsepower requirement Pronto 6 AS without DiscSystem (kW/hp)	---	125 / 170	---	140/190	---	132 / 180	---	147/200
Horsepower requirement Pronto 6 AS with DiscSystem (kW/hp)	---	147 / 200	---	184/250	---	162 / 220	---	184/250
Horsepower requirement Focus TD 3-point (kW/hp)	---	221 / 300	---	257/350	---	---	---	---
Horsepower requirement Focus ST 3-point (kW/hp)	---	184 / 250	---	---	---	---	---	---
Implement attachment 3-point	3-point Cat. II/III	3-point Cat. II/III	3-point Cat. II/III	3-point Cat. II/III	3-point Cat. II/III	3-point Cat. II/III	3-point Cat. II/III	3-point Cat. II/III